



## Humidity transmitters

### HT2WAD

<b>Sensor type:</b>	Capacitive
<b>Output signal:</b>	0÷1Vdc
<b>Range:</b>	0% ÷ 100%r.H
<b>Accuracy:</b>	±5%r.H. (25% ÷ 75%r.H.)
<b>Sheath:</b>	Ø14x40mm
<b>Protection:</b>	IP65 (electronics)
<b>Operating temperature:</b>	0÷75°C (sensor) / 0÷50°C (electronics)
<b>Dimensions of the enclosure:</b>	110x53x75mm (electronics)
<b>Power supply:</b>	12Vdc, 0.2W

### HD9513TC

<b>Sensor type:</b>	Capacitive
<b>Output signal:</b>	0÷1Vdc
<b>Range:</b>	5÷98% r.H.
<b>Accuracy:</b>	±2.5%r.H. @ 20°C
<b>Response time:</b>	2 minutes
<b>Sheath:</b>	Ø14x150mm; Pvcan plastic
<b>Cable:</b>	150cm, max 80°C, silicon rubber, 2 wires and screen
<b>Protection:</b>	IP64 (electronics)
<b>Operating temperature:</b>	-20÷80°C (probe) / -5÷50°C (electronics)
<b>Dimensions of the enclosure:</b>	120x80x55mm (electronics)
<b>Power supply:</b>	12÷24Vac/dc, 1VA